

Project No: **BDHRN002**Job Card No **0068**

Notif.No.: 10049067

Activity: **1002**

Rev No: 20000622

Model.: F900EX

Sheet 1 of 1

A/C Regn: **D-AHRN**

Serial No.: 096

Type: F900EX

Starting Phase: Routine

Starting Work Centre: FALCON A/C TEAM

Job Description: **INSP MLG Bays**

ETOPS A/C: No

RVSM A/C: No

Warranty: -

ATA: 53

Check Type: 1A+ Inspection

Work Center	
FALCON A/C	

Zone: 200,700**Access Required for this task:**

731AB,732AB,741AB,742AB,PAX

Corrective Action

0001	Task carried out in accordance with the attached Customer Card that quotes the Operator code detailed below.					 Order: 80069232 Operation: 0010 Phase: Routine - scheduling activity Work Center:FALCON A/C TEAM
	Accomplished		Inspected			
	Pers. No.	Date	Pers. No.	Date		
	Stamp		Stamp			

Completed & Confirmed on SAP IAW MOE 2.13.

Defect Card Raised

Components Removed/Installed

	Part Number	Part Name	S/N	Location	Comm. Off/On
OFF					
ON					
OFF					
ON					
OFF					
ON					
OFF					
ON					

Occurance Report Raised? YES ☐

Operations Above & Notifications Completed IAW MOE 2.13.



OEM Code: 53-40-00-200-804

Operator Code: 53-40-00-200-804-01

Form No: JA-SAP-MTX-002

Printed by: ADAMOVIC G



Printed: 03.09.2012

13:34:17

Print No: 1

Operator: **HERON AVIATION**

Work Card No.: **53-40-00-200-804-01C**

Serial No.: **096**

Model: **FALCON 900EX**

Reg No.: **D-AHRN**

Workorder No.: _____

	Date	A/C HRS	AFL	APH			
Due At	27-OCT-2012						
Accomplished							

TECHNICIAN SIGNATURE: _____ KIND OF CERTIFICATE & NO.: _____

INSPECTED BY: _____ KIND OF CERTIFICATE & NO.: _____

TECH	INSP	LABOR-HRS HRS.MINS
------	------	-----------------------

53-40-00-200-804-01 ☐ INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS

REMARKS : _____

AMM 53-40-00-200-804

>53-40-00-200-804-01C ☐ INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS
CPCP

REMARKS : _____

AMM 53-40-00-200-804

Operator: **HERON AVIATION**

Work Card No.: **53-40-00-200-804-01C**

Serial No.: **096**

Model: **FALCON 900EX**

Reg No.: **D-AHRN**

Workorder No.: _____

ACCESS PANEL SUMMARIES

731AB LH LOWER DOORS DOOR

53-40-00-200-804-01 INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS

741AB RH LOWER DOORS DOOR

53-40-00-200-804-01 INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS

AREA SUMMARIES

L1 LH L/G AND COMPARTMENT

53-40-00-200-804-01 INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS

SOURCE SUMMARIES

956 MPD 05-10-53 PAGE NO.:PAGE 3/5 REF: 53-40 T34 LOWER SECTION DATE: MAR 09/2012 2

53-40-00-200-804-01 INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS

956 MPD 05-15 ANNEX 1 PAGE NO.:1/2 REF: STANDARD AIRCRAFT BASELINE CPCP DATE: MAR 9/2012 2

53-40-00-200-804-01 INSPECTION OF THE LEFT MAIN LANDING GEAR (MLG) BAYS

C

FALCON 900EX AIRCRAFT MAINTENANCE MANUAL

TASK 53-40-00-200-804 INSPECTION OF THE MLG BAYS

WARNING:

- **CHECK THAT HYDRAULIC PRESSURE IS DROPPED.**
- **CHECK THAT THE AIRCRAFT SYSTEMS ARE NOT ENERGIZED.**

1. OVERVIEW OF THE JOB

Operation codes:

- 53-40-00-200-804-01 LH MLG bay
- 53-40-00-200-804-02 RH MLG bay

2. LOGISTICS

A. References

Reference	Designation
• 20-32-00-910-802	ACCEPTANCE CRITERIA FOR HYDRAULIC LEAKS
• 20-90-00-200-801	INSPECTION / CHECK OF ELECTRICAL AND ELECTRONIC SYSTEMS
• 27-00-00-220-801	VISUAL INSPECTION OF FLIGHT CONTROL HYDRAULIC COMPONENTS FOR EXTERNAL LEAKS
• 32-10-00-860-801	MANUAL OPENING / CLOSING OF THE MLG DOORS
• 32-44-21-820-801	CHECK / ADJUSTMENT OF THE BRAKE SWIVEL COUPLING ALIGNMENT

B. Ingredients and Consumable Products

Designation	Additional designation
• LUBRICATING OIL	
• SCOTCH BRITE	MIL-A-9162

C. Access

Reference	Designation
• 731AB	LH MLG MAIN DOOR
• 732AB	LH MLG STRUT DOOR
• 741AB	RH MLG MAIN DOOR
• 742AB	RH MLG STRUT DOOR
• PAX	PASSENGER DOOR

3. PRELIMINARY STEPS

- A. Manually open main landing gear (L/G) doors ([731AB](#)) and ([741AB](#)) (Refer to [TASK 32-10-00-860-801](#), paragraph "Manual Opening of Main Landing Gear Doors").

FALCON 900EX AIRCRAFT MAINTENANCE MANUAL

4. STRUCTURE

- A. Check paint for condition (flaking).
- B. Check visible portion of structure for absence of corrosion and distortions, and condition of rivet assembly.
- C. Check seals and door sealing brushes for condition.

5. ELECTRICAL CIRCUITS

CAUTION: TAKE ALL SAFETY PRECAUTIONS REQUIRED WHEN CHECKING ELECTRICAL CIRCUITS (REFER TO TASK 20-90-00-200-801).

- A. Visually check wiring and corresponding attachment for:
 - cleanliness, change of appearance, ageing, deterioration by external agents, overheating, abrasion, distortions, markings.
- B. Check that wiring does not contact the structure, including flat surfaces or piping.

A/C without SB F900EX-139 : check routing and absence of interference of wiring of door actuator proximity sensors (L6GA1)/(R6GA1).

A/C with SB F900EX-139 : check that the wiring of door actuator proximity sensors (L6GA1)/(R6GA1) is routed between the wiring retaining rod and the structure.
- C. Check correct connection of connectors.

6. FIRE EXTINGUISHING SYSTEM

- A. Check detector (L22WG)/(R22WG) for condition and attachment.
- B. Check the condition of detector connecting lugs (no break nor incipient break). If protecting sleeves are fitted to the lugs, implement SB F900EX-080 .

7. FLIGHT CONTROLS

- A. Check in RH main L/G compartment
 - (1) Check external condition of the following items of equipment:
 - middle airbrake solenoid selector valve (2CD),
 - inboard and outboard airbrake solenoid selector valve (3CD),
 - airbrake pressure holding check valve (503CD),
 - airbrake accumulator pressure gage (504CD),
 - airbrake charging valve (505CD),
 - slats outboard emergency solenoid selector valve (R3CM),
 - RH flap double angle drive (R503CG).
 - (2) Check for absence of corrosion at:
 - hydraulic couplings,
 - equipment attachment fittings.

FALCON 900EX AIRCRAFT MAINTENANCE MANUAL

NOTE: Traces of corrosion on the equipment can be removed with scotch brite.

- (3) Protect cleaned parts with lubricating oil.
- (4) Wipe any excess oil.
- (5) Check external leaktightness (no hydraulic fluid leakage) of airbrakes solenoid selector valves and pressure holding valve. If traces of hydraulic fluid are evidenced on the equipment or in the L/G compartment, carry out a static and dynamic sealing test (Refer to TASK 27-00-00-220-801).

B. Check in LH main L/G compartment

- (1) Check external condition of the following items of equipment:
 - reducing gear motor (3CG),
 - LH flap double angle drive (L503CG).
- (2) Repeat the checks described in steps 1. B. to 1. E.

8. HYDRAULIC SYSTEM

- A. Check piping for condition and attachment (tightening of clamps and harnesses, absence of friction against structure).
- B. Check equipment couplings for leaks.

NOTE: In case of doubt, about criteria of permissible hydraulic leaks (Refer to TASK 20-32-00-910-802).

- C. Check that hoses do not rub against the surrounding items of equipment.

9. LANDING GEARS AND DOORS

- A. At the top of landing gear leg (L2GF)/(R2GF), check that the charging/filling valve is provided with its protective blanks.
- B. At the bottom of the box structures and of the shock absorbers, check for traces of hydraulic fluid.
- C. Check wheel brake pistons for leaks.

NOTE: In case of doubt, about criteria of permissible hydraulic leaks (Refer to TASK 20-32-00-910-802).

- D. Check for alignment of the landing gear swivel couplings. If suspect (Refer to TASK 32-44-21-820-801). Check for condition of the brake unit supply hoses.
- E. Check for condition of:
 - landing gear legs and proximity sensors (L2GF1)/(L2GF2)-(R2GF1)/(R2GF2),
 - brace strut actuator (L12GA)/(R12GA) and connection of proximity sensors (L12GA1)/(L12GA2)-(R12GA1)/(R12GA2),
 - door actuator (L6GA)/(R6GA) and connection of proximity sensors (L6GA1)/(R6GA1),
 - landing gear uplock (L7GA)/(R7GA),
 - door uplock (L14GA)/(R14GA).

FALCON 900EX AIRCRAFT MAINTENANCE MANUAL

- F. In LH landing gear compartment, check landing gear and door hydraulic supply unit (**9GA**) for condition, attachment and absence of traces of hydraulic fluid.
- G. Check for absence of traces of hydraulic fluid at the level of connection with other equipment items.
- H. Check sliding rods for cleanliness.
- I. Check hinge and attachment fittings of main doors (**731AB**) /(**741AB**) for condition, absence of delamination or traces of impact.
- J. Check strut door (**732AB**) /(**742AB**) and landing gear leg link rods for condition, hinging, attachment, absence of delamination or traces of impact.
- K. Check safetyings for condition and efficiency (pins, piping, etc.).
- L. Check bonding braids for condition.

10. ANTI-ICING CIRCUIT

- A. Check anti-icing circuit lines for overall condition (lagging, attachment, overheating).

11. FINAL STEPS

- A. Manually close main landing gear (L/G) doors (**731AB**) and (**741AB**) (Refer to **TASK 32-10-00-860-801**, paragraph "Closing of Main Landing Gear Doors").